

iPP 310

The multi-payment PIN pad making merchants' lives easier

- Provide checkout autonomy, security and speed.
- Accept NFC/contactless payment quickly and simply.
- Connect to an iCT 2xx terminal in seconds with seamless plug & play installation.



security



smartcard



magstripe



contactless

The iPP 310 makes merchants' lives easier by making all payment transactions, including contactless, faster.

Highest Security

The iPP 310 meets the highest security requirements. PCI PTS 3.x certified, and ensures secure data and application management while enabling highly secured electronic transactions. The optional PIN privacy shield provides additional confidentiality at PIN entry.

All Payment Options

In addition to accepting EMV chip & PIN, magstripe & NFC/contactless payment, the iPP 310 also enables new NFC loyalty, couponing and wallet programs.

Designed for Ease-of-Use

Among the world's smallest and lightest devices, the iPP 310 is designed for easy handling and robust daily use. The backlit keypad and outstanding LCD display readability make PIN entry and operations very intuitive. Large keys and powerful buzzer speed transactions while reducing PIN entry errors. Visual indicators simplify contactless payment for both consumers and merchants.

Easy Connectivity

With its USB connection, compact size and single cable, the iPP 310 is easy to integrate into the iCT200 Series.

Telium 2

Powered by the Ingenico Group, Telium 2 technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium 2 is the world's best platform to provide payment services. It provides a fully scalable, reliable operating system embedded into the 27 million terminals deployed worldwide.



Feature	Description	
Processor	ARM 9 & ARM 7	●
Memory	16 MB SDRAM, 16 MB Flash	●
Card reader	Smart card Magstripe Contactless reader	● ● ●
Display		LCD monochrome 128 x 64 white backlit
Keypad	Backlit operational keys Navigation keys	15 4
Audio	Buzzer	●
Terminal connections		1 USB slave
Power	Powered USB	5V 500 mA
Terminal size	L x W x H	6.61" x 3.26" x 1.57"
Weight		9.52 oz
Environment	Operating temperature Storage temperature Relative humidity, non condensing	41°F to 113°F -4°F to 158°F 85% HR to 104°F
Accessories	USB cable from iCT 200 Series to IPP 310 Clippable PIN shield	Option Option
Customization	Lens marking Top casing	Option Option
Security	Online & Offline	PCI PTS 3.x certified

CORP-BR-IPP 310. All rights reserved. This document is not binding and the specifications above can be modified without prior consent. ©2015



www.ingenico.us